


Small Signal Schottky Diode



SOD123

Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- V_{RRM} 60V/50V/40V
- I_{FAV} 0.07A
- Part no. with suffix "Q" means AEC-Q101 qualified

Applications

- For Surface Mount Application
- Automotive

Mechanical Data

- **Case:** SOD123
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Polarity:** Cathode line denotes the cathode end

■ Maximum Ratings ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	CONDITIONS	VALUE	
Repetitive peak reverse voltage	V_{RRM}	V		SD101AWQ	60
				SD101BWQ	50
				SD101CWQ	40
Average Forward Current	I_{FAV}	A		0.07	
Peak Forward Surge Current	I_{FSM}	A	8.3ms, half sine	3	
Power Dissipation	P_{tot}	mW		450	
Thermal Resistance Junction to Ambient	R_{thJA}	K/W		278	
Junction Temperature	T_J	$^{\circ}\text{C}$		-55 to +150	
Storage Temperature Range	T_{stg}	$^{\circ}\text{C}$		-55 to +150	



SD101AWQ & SD101BWQ & SD101CWQ

■ Electrical Characteristics (T_a=25°C Unless otherwise specified)

PARAMETER	SYMBOL	UNIT	CONDITIONS	PART	MIN	MAX
Forward Voltage	V _F	V	I _F =1mA	SD101AWQ		0.41
				SD101BWQ		0.4
				SD101CWQ		0.39
			I _F =15mA			1
Reverse Leakage Current	I _R	uA	V _R =50V	SD101AWQ		0.2
			V _R =40V	SD101BWQ		0.2
			V _R =30V	SD101CWQ		0.2
Reverse Breakdown Voltage	V _{BR}	V	I _R =10uA	SD101AWQ	60	
				SD101BWQ	50	
				SD101CWQ	40	
Junction Capacitance	C _J	pF	V _R =1V, f=1MHz			4
Reverse Recovery Time	t _{rr}	ns	I _F =I _R =10mA, I _{rr} =1mA, R _L =100Ω			3

■ Ordering Information (Example)

PREFERED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SD101AWQ& SD101BWQ& SD101CWQ	F2	Approximate 0.010	3000	30000	120000	7" reel



SD101AWQ & SD101BWQ & SD101CWQ

■ Characteristics (Typical)

Fig.1: P_D-T_A




Fig.2: Capacitance Characteristics




Fig.3: Forward Characteristics






Fig.4: Reverse Characteristics






SD101AWQ & SD101BWQ & SD101CWQ

■ Outline Dimensions



DIMENSIONS				
DIM	INCHES		MM	
	MIN	MAX	MIN	MAX
A	0.140	0.152	3.550	3.850
B	0.100	0.112	2.550	2.850
C	0.055	0.071	1.400	1.800
D	0.037	0.053	0.950	1.350
E	0.020	0.028	0.510	0.710
G	0.006	0.018	0.150	0.450
H	0.003	0.010	0.080	0.250
J	0.000	0.006	0.000	0.150
θ	0	8°	0	8°

■ Marking Information



	Marking
SD101AWQ	S1
SD101BWQ	S2
SD101CWQ	S3

Note:

1. All marking is at middle of the product body
2. All marking is in laser marking
3. XX. is Marking Code
4. Body color: Black



SD101AWQ & SD101BWQ & SD101CWQ

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, life-sustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.